



9.00x22.5 ET162

ET 162 / ET 161

Anwendung:

- Trailer
- Semi-Trailer
- Truck
- Bus

TECHNISCHE DATEN

TEP-Nr.	TEPAA228963052	TEPAA229100214
Radgröße	9.00x22.5	9.00 x 22
Rad-Ausführung	BMZ (Ø 26) (outboard valve)	BMZ (Ø 26) AV (outboard valve)
Beschichtung	Wet coating	Powder coating
Mittenloch	281 mm	281 mm
Bolzenlochkreis	335 mm	335 mm
Bolzenlochanzahl	10	10
Einpresstiefe	162	161
Gewicht	43.1	41 kg
Tragkraft	4.000 kg	4.000 kg
Zwillingsmontage	yes	yes

REIFENGRÖSSEN

12 R 22.5

13 R 22.5

295/55 R 22.5

295/60 R 22.5

95/80 R 22.5

305/70 R 22.5

315/60 R 22.5

315/70 R 22.5

315/80 R 22.5

- High quality level and standards in accordance with the European EUWA / ETRTO standard
- TÜV-tested and TÜV-monitored
- With 'Powered by Germany' designation
- Valve already fitted on delivery
- Also available with M6 thread for TPMS
- Available as a complete wheel
- Has been subjected to further tests with OEM requirements e.g. salt spray test